


Formstücke

Doppelflanschbogen (FFK- und FFQ-Stücke)



Pos.	DN	Wand- dicke e mm	L mm	Grad- zahl	Gewicht mit ZMA und Bitumen kg/Stück	Gewicht mit EKB- Beschichtung kg/Stück
1	100	7,2	180	90°	12,6	12,0
2	100	7,2	140	45°	12,5	11,9
3	100	7,2	140	30°	12,5	11,9
4	100	7,2	140	22°30'	12,5	11,9
5	100	7,2	140	11°15'	12,5	11,9
6	125	7,5	200	90°	16,5	15,6
7	125	7,5	150	45°	16,3	15,3
8	125	11,1	225	30°	16,3	15,3
9	125	7,5	225	22°30'	16,3	15,3
10	125	7,5	225	11°15'	16,3	15,3
11	150	7,8	220	90°	21,0	19,8
12	150	7,8	160	45°	20,5	19,5
13	150	7,8	160	30°	20,5	19,5
14	150	7,8	160	22°30'	20,7	19,7
15	150	7,8	160	11°15'	20,0	19,0
16	200	8,4	260	90°	33,0	31,2
17	200	8,4	180	45°	30,5	29,0
18	200	8,4	180	30°	30,5	29,0
19	200	8,4	180	22°30'	30,5	29,0
20	200	8,4	180	11°15'	27,5	26,0

Doppelflanschbogen (FFK- und FFQ-Stücke)

Pos.	DN	Wand- dicke e mm	L mm	Grad- zahl	Gewicht mit ZMA und Bitumen kg/Stück	Gewicht mit EKB- Beschichtung kg/Stück
21	250	9,0	350	90°	58,0	54,5
22	250	9,0	350	45°	53,0	50,0
23	250	9,0	210	30°	43,5	41,5
24	250	9,0	210	22°30'	43,5	41,5
25	250	9,0	210	11°15'	43,5	41,5
26	300	9,6	400	90°	81,0	76,2
27	300	9,6	400	45°	74,1	70,0
28	300	9,6	255	30°	63,0	60,0
29	300	9,6	255	22°30'	63,0	60,0
30	300	9,6	255	11°15'	63,0	60,0