


Formstücke

Doppelmuffenbogen (MMK- und MMQ-Stücke)



Pos.	DN	Wand- dicke e	Lu Serie A	Grad- zahl	Gewicht mit ZMA und Bitumen	Gewicht mit EKB- Beschichtung
		mm	mm		kg/Stück	kg/Stück
1	100	7,2	120	90°	13,2	12,8
2	100	7,2	65	45°	11,5	11,2
3	100	7,2	50	30°	11,0	10,8
4	100	7,2	40	22°30'	10,2	10,0
5	100	7,2	30	11°15'	10,0	9,9
6	125	7,5	145	90°	18,6	18,0
7	125	7,5	75	45°	17,8	17,5
8	125	7,5	60	30°	16,6	16,0
9	125	7,5	50	22°30'	16,2	16,0
10	125	7,5	35	11°15'	15,2	15,0
11	150	7,8	170	90°	22,5	21,6
12	150	7,8	85	45°	19,4	18,5
13	150	7,8	65	30°	18,4	18,0
14	150	7,8	55	22°30'	17,7	17,4
15	150	7,8	35	11°15'	15,5	15,3
16	200	8,4	220	90°	33,5	32,0
17	200	8,4	110	45°	31,7	30,2
18	200	8,4	80	30°	28,0	27,5
19	200	8,4	65	22°30'	27,0	26,5
20	200	8,4	40	11°15'	25,5	24,7