


Formstücke

Muffenbogen (MK- und MQ-Stücke)

(nach FGR-Werknorm 70)



Pos.	DN	Wand-	Lu	Grad-	Gewicht	Gewicht
		dicke				
		e		zahl	Bitumen	Beschichtung
		mm	mm		kg/Stück	kg/Stück
1	100	7,2	120	90°	12,1	11,2
2	100	7,2	65	45°	10,8	9,9
3	100	7,2	50	30°	10,4	9,4
4	100	7,2	40	22°30'	10,2	9,2
5	100	7,2	30	11°15'	9,8	8,8
6	125	7,5	145	90°	17,5	16,1
7	125	7,5	75	45°	15,1	13,8
8	125	7,5	60	30°	14,4	13,1
9	125	7,5	50	22°30'	14,0	12,7
10	125	7,5	35	11°15'	13,4	12,1
11	150	7,8	170	90°	23,5	21,5
12	150	7,8	85	45°	20,0	18,3
13	150	7,8	65	30°	18,9	17,2
14	150	7,8	55	22°30'	18,4	16,7
15	150	7,8	35	11°15'	17,4	15,7
16	200	8,4	220	90°	38,0	35,0
17	200	8,4	110	45°	31,5	28,5
18	200	8,4	80	30°	29,0	26,5
19	200	8,4	65	22°30'	28,0	25,5
20	200	8,4	40	11°15'	26,5	24,0

Muffenbogen (MK- und MQ-Stücke)

(nach FGR-Werknorm 70)

Pos.	DN	Wand- dicke	Lu	Grad- zahl	Gewicht mit ZMA und Bitumen	Gewicht mit EP- Beschichtung
		mm	mm		kg/Stück	kg/Stück
21	250	9,0	270	90°	74,0	70,0
22	250	9,0	130	45°	46,0	42,0
23	250	9,0	105	30°	41,0	37,0
24	250	9,0	75	22°30'	40,0	36,0
25	250	9,0	50	11°15'	37,0	33,0
26	300	9,6	320	90°	101,0	96,0
27	300	9,6	150	45°	66,5	61,5
28	300	9,6	115	30°	61,0	56,0
29	300	9,6	85	22°30'	58,5	53,5
30	300	9,6	55	11°15'	54,0	49,0